



# Standard bull's eye windows

All our referenced bull's eye windows are supplied for facades or with slopes and flanges. This range is available in defined dimensions and models in natural zinc, QUARTZ-ZINC®, ANTHRA-ZINC®, AZENGAR® and copper. The models are for new or refurbished buildings which may require modifications of the existing wood structure. Optional keys are offered (see page 18).



3020



3022



3023




3026



3065



3066




3067



4205



4206



4211

Reference	Opening in m	Overall length in m		Mounted key
		Height	Width	
3020 and 3021*	0.60 x 0.40	0.97	0.95	2281/028
	0.65 x 0.50	1.04	1.06	2282/040
	0.70 x 0.50	1.13	1.16	2282/040
	0.80 x 0.60	1.29	1.31	2282/040
	0.90 x 0.60	1.40	1.31	2282/040
3022	0.60 x 0.40	0.96	1.00	-
	0.65 x 0.50	1.03	1.12	-
	0.70 x 0.50	1.08	1.12	-
	0.80 x 0.60	1.21	1.27	-
	0.90 x 0.60	1.31	1.27	-
3023	Ø 0.75	1.23	1.27	-
3024 and 3025*	0.50 x 0.40	0.95	0.78	0605/032
	0.65 x 0.50	1.18	1.00	0605/032
	0.70 x 0.50	1.23	1.00	0605/032
	0.80 x 0.60	1.38	1.w10	2282/040
	0.90 x 0.60	1.48	1.16	2282/040
3026	Ø 0.75	1.18	1.28	-
3065	Ø 0.25	0.46	0.46	-
3066	Ø 0.35	0.86	0.86	-
	Ø 0.40	0.98	0.98	-
	Ø 0.45	1.02	1.02	-
	Ø 0.50	1.07	1.07	-
	Ø 0.60	1.23	1.23	-
	Ø 0.65	1.32	1.32	-
	Ø 0.75	1.43	1.43	-
3067	0.65 x 0.50	1.20	1.10	-
	0.70 x 0.55	1.20	1.10	-
	0.80 x 0.60	1.35	1.23	-
	0.90 x 0.60	1.47	1.23	-
4205	Ø 0.25	0.49	0.54	-
	Ø 0.28	0.53	0.58	-
	Ø 0.32	0.57	0.62	-
	Ø 0.38	0.69	0.74	-
	Ø 0.60	1.07	1.16	-
4206	0.45 x 0.32	0.74	0.72	-
	0.65 x 0.50	1.07	1.11	-
	0.70 x 0.50	1.12	1.11	-
	0.80 x 0.60	1.20	1.32	-
4211	0.90 x 0.60	1.40	1.32	-
	Ø 0.50	1.08	1.16	-
	Ø 0.60	1.30	1.39	-
	Ø 0.75	1.52	1.65	-
	Ø 0.90	1.94	2.08	-

\*: identical to previous model without frontal key